UNITED STATES PATENT AND TRADEMARK OFFICE **CERTIFICATE OF CORRECTION**

PATENT NO. : 6,945,328 B2

DATED : September 20, 2005

INVENTOR(S): Brian Cruickshank, et al.

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 4,

Line 60, after "anchor" insert -- 40 --.

Line 67, after "packer" insert -- or anchor 40 located --.

Column 5,

Line 54, after "packer" insert -- or anchor 40 --.

Line 56, replace "pressure applied to the tool to set the packer." with -- pressure applied to the tool to set the packer or anchor 40. --.

Lines 56-60, replace the sentence "Once the packer has been set and the set confirmed by applying a vertical load to the packer, fluid pressure is increased until a sufficient hydraulic force is generated on the locking member to shear the shear ring." with -- Once the packer or anchor 40 has been set and the set confirmed by applying a vertical load to the packer or anchor 40, fluid pressure is increased until a sufficient hydraulic force is generated on the locking member to shear the shear ring. --. Line 66, after "packer" insert -- or anchor 40 --.

Signed and Sealed this

Page 1 of 1

Sixth Day of December, 2005

JON W. DUDAS Director of the United States Patent and Trademark Office